



DYNAMIC TURBO C

Diesel Engine Oil for Pickup Trucks

Product Descriptions

- *DYNAMIC TURBO C* : A multigrade SAE 10W-30 diesel engine oil exceeding the requirements of API CF-4, especially developed for new model diesel engines of pickup trucks.

Features/Benefits

- Provides good lubrication, engine wear protection and reduces energy loss from friction of the engine parts
- Good cleansing property and soot-dispersing, free from soot accumulation, sludge and deposit formation, and ring sticking problem
- Endures to damage from heat and oxygen
- Prolongs engine life

Applications

- Recommended for use in pickup diesel engines under light and heavy duty conditions
- Suitable for cars with supercharger or turbocharger in all driving conditions including the small diesel engines requiring API CF-4 or lower performance level

Performance Standards

- API CF-4, CF / SG
- ACEA E2
- MB 228.1
- Mack EO-K/2
- Allison C4

Key Properties

	SAE 10W-30
- Viscosity @ 100 °C, cSt	11.2
- Viscosity @ 40 °C, cSt	72.3
- Viscosity Index	148
- Cold-cranking Simulator @ -25°C, cP	5,612
- Total Base Number, mgKOH/g	10.7
- Pour Point , °C	-18
- Flash Point (COC), °C	236
- Density @ 15 °C, g/cm ³	0.874
- Sulfate Ash (%wt.)	1.45

For more information, please contact Lubricants Technical Services Division, PTT Public Company Limited : Tel. (662) 239-7911, (662) 239-7985
Fax. (662) 239-7858 Lube Hot Line (662) 239-7878