



# CHALLENGER 4T-AT

## Semi-Synthetic, 4T Automatic Motorcycle Engine Oil

### Product Description

- **CHALLENGER 4T-AT** : High performance, semi-synthetic multigrade SAE 10W-40 four-stroke motorcycle oil exceeding the performance level of API SG and JASO MB. Specifically formulated from selected high quality synthetic base fluids and additives for automatic transmission four-stroke motorcycle with the Drivability Test, Full Load Power Test and Acceleration Test proved and the certified Motorcycle Four Cycle Gasoline Engine Oil Performance Classification "JASO MB".

### Features/Benefits

- Blended with special friction modifier "Molybdenum" to help maximize lubricity, quicker acceleration response and anti-wear protection
- Provides excellent thermal and oxidation stability
- Offers extra engine's part cleanliness and soot protection
- Prolongs engine life and drain interval

### Applications

- Recommended for CVT technology and new model of automatic transmission four-stroke motorcycle engines, such as YAMAHA and HONDA

### Reference Standards

- JASO MB (JASO Identification No. M066PTT005)
- API SG

### Key Properties

	SAE 10W-40
- Viscosity @ 100 °C, cSt	14.3
- Viscosity Index	160
- Cold-cranking Simulator, @ -25 °C, cP	6,226
- Flash Point , (COC) , °C	220
- Pour Point , °C	-30

For more information, please contact Fuels & Lubricants Research Department, PTT Research & Technology Institute : Tel. (662) 537-3000 Ext. 8182, 8278  
Fax. (662) 537- 3000 Ext. 8199, 8283 or Technical Service Division, Oil Business : Tel. (662) 537-2327-8, (662) 537-2408, (662) 537-2412.