

# Diesel Engine Oil for Agricultural Equipments

# **Product Descriptions**

- DYNATRAC: A multigrade SAE 15W-40 diesel engine oil exceeding the requirements of API CF-4/SG, formulated from high quality mineral base stocks and a selected additive to provide good protection for specially use with agricultural equipments.

## Features/Benefits

- Provides outstanding lubrication, engine wear protection and reduces energy loss from friction of the engine part
- Offer stronger oil film as well as prevents the build-up deposit, sludge and varnish
- Fortified very good detergency and soot dispersancy for preventing deposit accumulation and ring sticking problem

## **Applications**

- Recommended for all diesel powered engines which operate under both of heavy and severe duty or in the severe traffic conditions, including high speed turbocharged engines
- Mixed fleets of both diesel and gasoline engines requiring API CF-4 or SG performance lubricants

### Performance Standards

- API CF-4 / CF / SG

- MB 228.1

- ACEA E2

- MAN 271

- MACK EO-K/2

- ALLISON C-4

Key	Properties

	SAE 15W-40
- Viscosity @ 100 °C, cSt	14.7
- Viscosity Index	142
- Cold-cranking Simulator @ -20 °C, cP	6,130
- Flash Point, (COC), °C	234
- Pour Point, °C	-24
- Total Base Number, mg KOH/g	10.5

For more information, please contact Lubricants Technical Services Division, PTT Public Company Limited: Tel. (662) 239-7907-08, (662) 239-7910-11 Fax (662) 239-7858 or Lube Hot Line (662) 239-7878