



POWERTRAC SUPER PLUS

Premium Universal Tractor Transmission Oil (UTTO)

Product Description

- **POWERTRAC SUPER PLUS** : premium Universal Tractor Transmission Oil (UTTO) for hydraulic systems, gear, gear wheel and wet brake systems for agricultural tractors and pushcarts, produced from high quality mineral base oil and high performance multi-functional additive technology

Features/Benefits

- Provides high working efficiency of clutch and wet brake system without slipping and loud noise
- Prevents rust, corrosion and foam formation, good water resistance
- Inhibits to oxygen combination and thermal decomposition
- Reduces wear formation and Optimizes friction system
- Gives smooth hydraulic working, no filter plugging in the hydraulic system
- Extends the service life of engine
- Provides dual wear protection for gears & bearings and for yellow metals in the equipments

Applications

- Recommended for using with agricultural tractors, pushcarts and off-road equipment, besides using for hydraulic systems, it was also used with gear wheels, rear axles, power steering and wet brake systems.

Note : POWERTRAC SUPER PLUS is not eligible to use as tractor engine oil, DYNATRAC T-300 is recommended for single grade engine oil and DYNATRAC T-500 for the multi grade engine oil

Reference Standards

- | | | |
|---|---------------------|-------------------------------|
| - John Deere J20A, J20B, J20C, J20D | - API GL-4 | - Ford M2C86B, M2C134D |
| - Caterpillar TO-2 | - Allison C-4 | - JCMAS HK P-041 |
| - Volvo WB101 (except motor grader rear axles) | - CNH MAT 3525/3526 | - Case MS 1204/1206/1207/1209 |
| - Massey Ferguson CMS M1127, M1135, M1141, M1143, M1145 | | |

Key Properties

- | | |
|----------------------------|-------|
| - Viscosity @ 40°C, cSt | 62.11 |
| - Viscosity @ 100 °C, cSt | 9.4 |
| - Viscosity Index | 132 |
| - Flash Point , (COC) , °C | 232 |
| - Pour Point , °C | -41 |

For more information, please contact Lubricants Technical Services Division, PTT Public Company Limited : Tel. (662) 239-7911, (662) 239-7985
Fax. (662) 239-7858 Lube Hot Line (662) 239-7878