

## Synthetic cutting fluid

Descriptions

- *PTT Hikut syn W 11*: The product is synthetic cutting fluids. It have a good lubricity and cooling properties. It is suitable for grinding and machining general metal. The concentrate color is yellow when dilute with water It have no color transparent.

**Special Properties** 

- Good cooling or remove heat during machining.
- Good rust and corrosion prevention.
- Resistance to foaming.
- Resistance to bacterial and fungal growth.
- It can dilute with tap water or soft water.
- No toxic substance such as Chlorine and Nitrate / Nitrite

Application

- Recommended concentration (%). (Dilution with water)

Metal / Process	Grinding	Drilling	Milling	Tapping
Cast Iron	4-5 %	5-6%	5-6%	6-8%
Mild Steel	4-5%	5-6%	5-6%	6-8%

	Typical Value
- Appearance	Yellow
- Viscosity @ 40 oC, cSt	4.88
- pH ( Dilution 1 : 20 )	9.8
- Rust test / IP287	3.0 % break point
- Emulsion stability / IP263	Pass
- Thermal stability / IP311	Good homogeneous
- Nitrate / Nitrite	none
- Chlorine	none

For more information, contact Fuel and Lubricant Department, PTT Research and Technology Institute, PTT Public Company Limited Tel 0-2537-3000 Ext 8182 and 8270 Fax 0-2537-3000 Ext 8146 Lts 8199

Product no. SP007, Rev. 00-59